



B6.12 CURB & GUTTER

P.C.C. SIDEWALK

Design Standards		
	R.O.W.	Pavement Width
Major Streets	100'	51'
Secondary Streets	80'	51'
Collector Streets	66'	39'
Minor Streets	66'	30'
Marginal Access Streets	40'	30'
Cul-de-sac	Meet requirements of minor street and turnaround as per Section 17.28.110 of Municipal Code	

2" HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50

MAJOR, SECONDARY, AND ALL ROADS IN INDUSTRIAL DISTRICTS:
 8" HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N50
 0.05 GAL/S.Y. BITUMINOUS MATERIAL PRIME COAT

COLLECTOR, MINOR, MARGINAL ACCESS, AND CUL-DE-SACS:
 5" HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N50
 0.05 GAL/S.Y. BITUMINOUS MATERIAL PRIME COAT

6" AGGREGATE BASE COURSE, TYPE B, CA-6 CRUSHED AGGREGATE, VIRGIN MATERIAL ONLY (CA-6 GRADE 8, CRUSHED LIMESTONE)



VILLAGE OF WHEELING
 ENGINEERING DIVISION
 2 COMMUNITY BOULEVARD
 WHEELING, IL 60090
 WWW.WHEELINGIL.GOV

ROADWAY PAVEMENT SECTION STANDARD

VILLAGE OF WHEELING
 SPECIFICATIONS AND DETAILS
 FILE LOCATION
 T:\ENGINEERING\STANDARDS

REVISIONS	
K.R.G.	04-01-10 AUTOCAD FILE
K.G.C.	07-27-10 AUTOCAD FILE
K.A.G.	01-08-18 STANDARDS TABLE
K.A.G.	06-11-20 CHANGED TO MIX D

DETAIL NO.

R-9