



- MATERIALS TO BE USED:**
- HOT MIX ASPHALT SURFACE COURSE, MIX, "C", N50
 - BITUMINOUS MATERIAL (PRIME COAT), 0.5 GAL/SY
 - HOT MIX ASPHALT BINDER COURSE, IL-19, N50
 - BITUMINOUS MATERIAL (PRIME COAT), 0.5 GAL/SY
 - AGGREGATE BASE COURSE, VIRGIN MATERIAL ONLY
 - 6 TO 6.5 OZ/SY WOVEN STABILIZER FABRIC AT DIRECTION OF VILLAGE ENGINEER

WHEELING STANDARD
COMBINATION CONCRETE
DEPRESSED CURB & GUTTER

NOTES:

1. MAY BE SUBJECT TO STATE OR COUNTY PERMIT.
2. ALL WORKMANSHIP AND MATERIALS SHALL COMPLY WITH MOST RECENT I.D.O.T. STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
3. PROOF ROLL REQUIRED UPON COMPLETION OF SUB GRADE AND BASE MATERIAL. ZERO DEFLECTION IS VILLAGE OF WHEELING STANDARD.



VILLAGE OF WHEELING
ENGINEERING DIVISION
2 COMMUNITY BOULEVARD
WHEELING, IL 60090
WWW.WHEELINGIL.GOV

PARKING LOT PAVEMENT STANDARD

VILLAGE OF WHEELING SPECIFICATIONS AND DETAILS	S.W.	03-16-00 AUTOCAD FILE	DETAIL NO.
FILE LOCATION	S.W.	09-18-01 PER COMMENTS	R-6
T:\ENGINEERING\STANDARDS	C.J.C.	11-27-07 AUTOCAD FILE	
	M.T.P.	01-14-10 H.M.A. RQMNTS.	

REVISIONS		
S.W.	03-16-00	AUTOCAD FILE
S.W.	09-18-01	PER COMMENTS
C.J.C.	11-27-07	AUTOCAD FILE
M.T.P.	01-14-10	H.M.A. RQMNTS.

DETAIL NO.
R-6